



Modello	Lunghezza [mm]	Potenza [W]	Temperatura Colore [K°]	Flusso Luminoso [lm]	Indice Resa Cromatica [Ra]	Efficienza Luminosa [lm/w]	Classe Efficienza Energetica
LEDbar.HeD.1910.0350.4K3.O.CM.xxxxP2	350	2,55	4350	267	90	97	F
LEDbar.HeD.1910.0400.4K3.O.CM.xxxxP2	400	2,98	4350	311	90	97	F
LEDbar.HeD.1910.0450.4K3.O.CM.xxxxP2	450	3,4	4350	356	90	97	F
LEDbar.HeD.1910.0500.4K3.O.CM.xxxxP2	500	3,8	4350	400	90	97	F
LEDbar.HeD.1910.0550.4K3.O.CM.xxxxP2	550	4,25	4350	445	90	97	F
LEDbar.HeD.1910.0600.4K3.O.CM.xxxxP2	600	4,67	4350	489	90	97	F
LEDbar.HeD.1910.0650.4K3.O.CM.xxxxP2	650	5,1	4350	534	90	97	F
LEDbar.HeD.1910.0700.4K3.O.CM.xxxxP2	700	5,52	4350	578	90	97	F
LEDbar.HeD.1910.0750.4K3.O.CM.xxxxP2	750	5,95	4350	623	90	97	F
LEDbar.HeD.1910.0800.4K3.O.CM.xxxxP2	800	6,37	4350	667	90	97	F
LEDbar.HeD.1910.0850.4K3.O.CM.xxxxP2	850	6,8	4350	712	90	97	F
LEDbar.HeD.1910.0900.4K3.O.CM.xxxxP2	900	7,22	4350	756	90	97	F
LEDbar.HeD.1910.0950.4K3.O.CM.xxxxP2	950	7,65	4350	801	90	97	F
LEDbar.HeD.1910.1000.4K3.O.CM.xxxxP2	1000	8,07	4350	845	90	97	F
LEDbar.HeD.1910.1050.4K3.O.CM.xxxxP2	1050	8,5	4350	890	90	97	F
LEDbar.HeD.1910.1100.4K3.O.CM.xxxxP2	1100	8,92	4350	934	90	97	F
LEDbar.HeD.1910.1150.4K3.O.CM.xxxxP2	1150	9,35	4350	979	90	97	F
LEDbar.HeD.1910.1200.4K3.O.CM.xxxxP2	1200	9,77	4350	1023	90	97	F

Specifiche cablaggio - Wiring specifications

xxxx = Lunghezza cavo - Cable length [mm]
P2 = DC Plug 5,5 mm [IP65]

