



Modello	Lunghezza [mm]	Potenza [W]	Temperatura Colore [K°]	Flusso Luminoso [lm]	Indice Resa Cromatica [Ra]	Efficienza Luminosa [lm/w]	Classe Efficienza Energetica
LEDbar.HeD.1910.0350.5K7.O.CM.xxxxP2	350	3,6	5700	402	90	103	F
LEDbar.HeD.1910.0400.5K7.O.CM.xxxxP2	400	4,2	5700	469	90	103	F
LEDbar.HeD.1910.0450.5K7.O.CM.xxxxP2	450	4,8	5700	536	90	103	F
LEDbar.HeD.1910.0500.5K7.O.CM.xxxxP2	500	5,4	5700	603	90	103	F
LEDbar.HeD.1910.0550.5K7.O.CM.xxxxP2	550	6	5700	670	90	103	F
LEDbar.HeD.1910.0600.5K7.O.CM.xxxxP2	600	6,6	5700	737	90	103	F
LEDbar.HeD.1910.0650.5K7.O.CM.xxxxP2	650	7,2	5700	840	90	103	F
LEDbar.HeD.1910.0700.5K7.O.CM.xxxxP2	700	7,8	5700	871	90	103	F
LEDbar.HeD.1910.0750.5K7.O.CM.xxxxP2	750	8,4	5700	938	90	103	F
LEDbar.HeD.1910.0800.5K7.O.CM.xxxxP2	800	9	5700	1005	90	103	F
LEDbar.HeD.1910.0850.5K7.O.CM.xxxxP2	850	9,6	5700	1072	90	103	F
LEDbar.HeD.1910.0900.5K7.O.CM.xxxxP2	900	10,2	5700	1139	90	103	F
LEDbar.HeD.1910.0950.5K7.O.CM.xxxxP2	950	10,8	5700	1206	90	103	F
LEDbar.HeD.1910.1000.5K7.O.CM.xxxxP2	1000	11,4	5700	1273	90	103	F
LEDbar.HeD.1910.1050.5K7.O.CM.xxxxP2	1050	12	5700	1340	90	103	F
LEDbar.HeD.1910.1100.5K7.O.CM.xxxxP2	1100	12,6	5700	1407	90	103	F
LEDbar.HeD.1910.1150.5K7.O.CM.xxxxP2	1150	13,2	5700	1474	90	103	F
LEDbar.HeD.1910.1200.5K7.O.CM.xxxxP2	1200	13,8	5700	1541	90	103	F

Specifiche cablaggio - Wiring specifications

xxxx = Lunghezza cavo - Cable length [mm]
P2 = DC Plug 5,5 mm [IP65]

