



Modello	Lunghezza [mm]	Potenza [W]	Temperatura Colore [K°]	Flusso Luminoso [lm]	Indice Resa Cromatica [Ra]	Efficienza Luminosa [lm/w]	Classe Efficienza Energetica
LEDbar.HeD.D16.0330.4K3.O.CP	330	2,55	4350	267	90	97	F
LEDbar.HeD.D16.0380.4K3.O.CP	380	2,98	4350	311	90	97	F
LEDbar.HeD.D16.0430.4K3.O.CP	430	3,4	4350	356	90	97	F
LEDbar.HeD.D16.0480.4K3.O.CP	480	3,8	4350	400	90	97	F
LEDbar.HeD.D16.0530.4K3.O.CP	530	4,25	4350	445	90	97	F
LEDbar.HeD.D16.0580.4K3.O.CP	580	4,67	4350	489	90	97	F
LEDbar.HeD.D16.0630.4K3.O.CP	630	5,1	4350	534	90	97	F
LEDbar.HeD.D16.0680.4K3.O.CP	680	5,52	4350	578	90	97	F
LEDbar.HeD.D16.0730.4K3.O.CP	730	5,95	4350	623	90	97	F
LEDbar.HeD.D16.0780.4K3.O.CP	780	6,37	4350	667	90	97	F
LEDbar.HeD.D16.0830.4K3.O.CP	830	6,8	4350	712	90	97	F
LEDbar.HeD.D16.0880.4K3.O.CP	880	7,22	4350	756	90	97	F
LEDbar.HeD.D16.0930.4K3.O.CP	930	7,65	4350	801	90	97	F
LEDbar.HeD.D16.0980.4K3.O.CP	980	8,07	4350	845	90	97	F
LEDbar.HeD.D16.1030.4K3.O.CP	1030	8,5	4350	890	90	97	F
LEDbar.HeD.D16.1080.4K3.O.CP	1080	8,92	4350	934	90	97	F
LEDbar.HeD.D16.1130.4K3.O.CP	1130	9,35	4350	979	90	97	F
LEDbar.HeD.D16.1180.4K3.O.CP	1180	9,77	4350	1023	90	97	F
LEDbar.HeD.D16.1230.4K3.O.CP	1230	10,2	4350	1068	90	97	F
LEDbar.HeD.D16.1280.4K3.O.CP	1280	10,62	4350	1112	90	97	F
LEDbar.HeD.D16.1330.4K3.O.CP	1330	11,05	4350	1157	90	97	F
LEDbar.HeD.D16.1380.4K3.O.CP	1380	11,47	4350	1201	90	97	F
LEDbar.HeD.D16.1430.4K3.O.CP	1430	11,9	4350	1246	90	97	F
LEDbar.HeD.D16.1480.4K3.O.CP	1480	12,32	4350	1290	90	97	F
LEDbar.HeD.D16.1530.4K3.O.CP	1530	12,75	4350	1335	90	97	F
LEDbar.HeD.D16.1580.4K3.O.CP	1580	13,17	4350	1379	90	97	F
LEDbar.HeD.D16.1630.4K3.O.CP	1630	13,6	4350	1424	90	97	F
LEDbar.HeD.D16.1680.4K3.O.CP	1680	14,02	4350	1468	90	97	F
LEDbar.HeD.D16.1730.4K3.O.CP	1730	14,45	4350	1513	90	97	F
LEDbar.HeD.D16.1780.4K3.O.CP	1780	14,87	4350	1557	90	97	F